# **REMS Power-Press XL ACC**

Universal, powerful power tool with automatic circuit control for making press joints of all common press fitting systems.

Pipe pressing joints

Ø 10 – 108 (110) mm

 $0^{3/8}-4^{-1}$ 

Complete range of REMS pressing tongs/pressing rings/ pressing rings XL for all common pressfitting systems, see page 188–222.

REMS Power-Press XL ACC – universal up to Ø 110 mm. Pressing of Ø 10 – 108 mm in just one action. Ultra-fast, e.g. Geberit Mapress stainless steel Ø 108 mm in only 15 seconds. With automatic circuit control. Automatic locking of pressing tongs.

#### System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses  $32\,kN$  and suitable radial presses of other makes with  $32\,kN$  thrust force.

All pressing tongs marked by a  $^{\star}$  have another connection and also fit the manual radial press REMS Eco-Press. Thus simple, inexpensive stocking.

# Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings/pressing rings XL for all common pressfitting systems (page 188–222). Highly durable pressing tongs/XL pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings/pressing rings XL are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs are required, as an accessory, for driving the REMS (PR) pressing rings.

## Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.5 kg. Long working stroke for pressings in a single action, ideal for large dimensions. Ultra-fast, e.g. Geberit Mapress stainless steel Ø 108 mm in only 15 seconds. Ergonomically designed housing with soft grip and recessed handle. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/ pressing rings. Adjustable hand guard.

#### Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

#### Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force  $32\,\mathrm{kN}$ . Powerful electro-hydraulic drive with proven universal motor  $450\,\mathrm{W}$ , robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.







German Quality Product

Tested by electrosuisse



# **Supply format**

**REMS Power-Press XL ACC Basic-Pack.** Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints Ø 10–108 (110) mm, Ø % – 4". For driving REMS pressing tongs/pressing rings/pressing rings XL and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Version	ArtNo.
In transport case XL.	579010
In XL-Boxx system case.	579012
Other voltages on request.	





## Accessories

REMS pressing tongs/pressing rings/pressing rings XL see page 188–222.			
Adapter tongs for other REMS pressing rings see page 222.			
Adapter tongs Z6 XL for driving REMS pressing rings 64.0-108.0 XL (PR-3S), 2½-4" XL (PR-3S) with REMS Power-Press XL ACC	579120		
REMS Power-Press XL ACC drive Unit	579000		
Description	ArtNo.		

REMS cropping tongs for threaded rods see page 225.

REMS cable snear for electric cable see page 225.		
Transport case XL with inlays and practical carrying		
handles	579240	
XL-Boxx system case with inserts	579601	

